


NAJMA

CONTACT ADHESIVE

Technical data sheet



DESCRIPTION	NAJMA Contact Adhesive superior quality universal, liquid contact Adhesive based on neoprene rubber. It is strong and long lasting, easy to use and highly suitable for universal application, it provides excellent flow and easy to use on any type of solid and dry floor.
APPLICATIONS & RECOMMENDATIONS:	Bond universal floor covering or stair carpets, moquette, hardboard, plastic edges, rubber, leather, linoleum, cork, textiles foams to itself as well as to wood, chipboard, concrete and metal. Excellent for bonding stair edgings, furniture or fells, among other things. Also for repairing shoes, bags, etc.
	
COMPOSITION	Blend of synthetic rubber-based polymer
USE OF THE SUBSTANCE / PREPAEATION	Solvent Based contact adhesive
COLOUR	Light brown
PACKAGING	3L Tin – 4 pieces per box
WEIGHT	2.5Kg
DRY EXTRACT (%)	22-24
OPEN TIME (MIN)	10 (at 20°C)
EVAPORATION TIME (MIN)	10 to 15
CONSISTENCY	Liquid, Brushable
STORAGE	Store in shaded, dry conditions between +5°C and 20°C
NECESSARY TOOLS	Paddle or spatula to stir adhesive and suitable trowel, spreader or brush to apply adhesive.
PREPARATION	Surfaces must be clean, dry, smooth, firm and free from any traces of contaminant which may affect adhesion.
APPLICATION	Stir the adhesive thoroughly before use. For ease of application, maintain at a temperature between +15°C and +24°C. <ul style="list-style-type: none">• Apply a uniform coating of adhesive to both surfaces using a serrated trowel, adhesive spreader or brush.

- Allow the solvents to evaporate until the adhesive is dry to the touch. This may take 10 to 20 minutes depending on the porosity of the materials, ambient temperature, humidity and the thickness of the deposited adhesive.
- Position coated surfaces accurately and press firmly to ensure overall contact.
- Mechanical pressing, even of very short duration, will always give superior results.
- Hand pressing by means of a flat wooden block lined with felt or hard rubber roller is sufficient for most applications.

PROTECTIVE EQUIPMENT

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

STORAGE & HANDLING

Store in a cool, dry and ventilation location. Keep away from heat, sparks, Flame and Other source of ignition.

Avoid contact with skin and eyes
 Application, processing: providing good ventilation and extraction.
 Keep away from heat, sparks and flame.
 Wash thoroughly after handling.
 Keep the container closed.
 Do not cut or weld on or near this container.

HEALTH & SAFETY PRECAUTIONS

Safety data sheet must be read and understood before use.
 Highly flammable - keep away from open flames and other ignition sources.
 For professional use only.

HAZARDS IDENTIFICATION



F ; Highly flammable



Xi ; Irritant



N ; Dangerous for the environment